

FireLock Sprinklers – Standard Commercial

Standard Commercial

Note: Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

Model No./SIN	K-Factor	Deflector Type	Response	Nom. Thread Size (in/NPT)	Temperature Rating (°F/°C)	Coatings and Finishes	Approvals and Listings 1	Sub. Pub.
V2703	5.6	Upright	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2707	5.6	Pendent	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2707	5.6	Recessed Pendent	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2704	5.6	Upright	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2708	5.6	Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2708	5.6	Recessed Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

LIGHT HAZARD, ORDINARY HAZARD, STORAGE*

V27 FRAME	V2709	5.6	Horizontal Sidewall	Standard	1/2	135F/57C	UL, ULC, FM, LPCB, CCC, VDE	
V2709	5.6	Recessed Horiz. Sidewall	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2710	5.6	Horizontal Sidewall	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2710	5.6	Recessed Horiz. Sidewall	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

CONVENTIONAL (OLD STYLE)

V27 FRAME	V2725	5.6	Pendent/Upright	Standard	1/2	135F/57C	UL, ULC, FM, LPCB, CCC, VDE	
V2726	5.6	Pendent/Upright	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

EUROPEAN PENDENT

V27 FRAME	V2727	5.6	Pendent	Standard	1/2	135F/57C	UL, ULC, FM, LPCB, CCC, VDE	
V2728	5.6	Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3423	8.0	Pendent	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3424	8.0	Pendent	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

V27 FRAME

V2701	2.8	Upright	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2702	2.8	Upright	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2705	2.8	Pendent	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2705	2.8	Recessed Pendent	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2706	2.8	Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2706	2.8	Recessed Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

V24 FRAME

V2401	4.2	Upright	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2402	4.2	Upright	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2403	4.2	Pendent	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2404	4.2	Pendent	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

FireLock Sprinklers – Specific Application

Specific Application

Note: Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

LIGHT HAZARD - CONCEALED SPACES

V2502	4.2	Upright	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
-------	-----	---------	-------	-----	----------	-------------	-----------------------------	--

FireLock Sprinklers – Storage

Storage

Note: Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

LP-46 LOW PRESSURE STORAGE SPRINKLER

V4601	25.2	Pendent	Standard	1	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V4603	25.2	Upright	Standard	1	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V4603	36.8	Upright	Standard	1	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

EARLY SUPPRESSION FAST RESPONSE

V4402	14.0	Pendent	Fast	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V4404	16.8	Pendent	Fast	20	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V4404	24.2	Pendent	Fast	20	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

ORDINARY HAZARD, STORAGE

V3407	11.2	Pendent	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3403	11.2	Upright	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3408	11.2	Pendent	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3404	11.2	Upright	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

INTERMEDIATE LEVEL - RACK STORAGE, ORDINARY HAZARD

V2723	5.6	Pendent	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2721	5.6	Upright	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2724	5.6	Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2722	5.6	Upright	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

V34 FRAME

V3419	11.5	Pendent	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3417	8.0	Upright	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3420	8.0	Pendent	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3418	11.5	Upright	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

Sprinkler finishes

Victaulic Part Identification	Finish
1	Plain Brass
2	Chrome
4	White (RAL 9010)
5	Wax
8	Nickel/Teflon
B	Black (RAL 9004)
G	Cream (RAL 9001)
-	Custom
W	Bright White (RAL 9003)



Our concealed cover plates can be matched to customer requested colors using our approved color chip chart. Ask your Victaulic sales representative about the hundreds of colors available.

* Teflon is a registered trademark of Dupont Corporation.

FireLock Sprinklers – Extended Coverage

Extended Coverage

Note: Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

EXTENDED COVERAGE LIGHT HAZARD

V3411	11.2	Pendent	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3411	11.2	Recessed Pendent	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3412	11.2	Pendent	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3412	11.2	Recessed Pendent	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3413	14.0	Pendent	Standard	20	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3413	14.0	Recessed Pendent	Standard	20	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3414	14.0	Pendent	Quick	20	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3414	14.0	Recessed Pendent	Quick	20	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3415	8.0	Horizontal Sidewall	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3415	11.5	Horizontal Sidewall	Standard	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3416	8.0	Horizontal Sidewall	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3416	11.5	Horizontal Sidewall	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

EXTENDED COVERAGE ORDINARY HAZARD

V3421	14.0	Pendent	Standard	20	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3421	14.0	Recessed Pendent	Standard	20	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3425	14.0	Upright	Standard	20	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

FireLock Sprinklers – Residential

Residential

Note: Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

RESIDENTIAL

V2738*	4.2	Horizontal Sidewall	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2738*	6.0	Recessed Horiz. Sidewall	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2730*	4.9	Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2730*	4.9	Recessed Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2732*	7.1	Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2732*	4.9	Recessed Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2734*	4.9	Concealed Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2736	7.1	Concealed Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2740	4.9	Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2740	4.9	Recessed Pendent**	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2740	4.9	Recessed Pendent***	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2742	7.1	Concealed Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

RESIDENTIAL - LOW FLOW ADJUSTABLE CONCEALED

V2744	5.6	Horizontal Sidewall	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2744	8.1	Recessed Horiz. Sidewall	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

RESIDENTIAL - LOW FLOW ADJUSTABLE CONCEALED

V3426	6.9	Pendent	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3426	9.9	Recessed Pendent	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

V38 FRAME

V3806	5.6	Concealed Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
-------	-----	-------------------	-------	-----	----------	-------------	-----------------------------	--

FireLock Sprinklers – Decorative

Decorative

Note: Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

RESIDENTIAL - ADJUSTABLE FLUSH

V2902*	4.1	Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V2902*	6.1	Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

ADJUSTABLE, CONCEALED, LIGHT AND ORDINARY HAZARD

V3801**	5.6	Concealed Pendent	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3802**	8.1	Concealed Pendent	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3807	5.6	300psi Conceal.	Standard	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
V3808	5.6	300psi Conceal.	Quick	1/2	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	

ADJUSTABLE, CONCEALED, EXTENDED COVERAGE, LIGHT HAZARD

V3904	8.0	Concealed Pendent	Quick	3/4	135F/57C	Plain Brass	UL, ULC, FM, LPCB, CCC, VDE	
-------	-----	-------------------	-------	-----	----------	-------------	-----------------------------	--

Notes

- * UL Listed to 250psi, FM Approved to 175 psi.
- † For K-Factor when pressure is measured in Bar, multiply 5.1 units by 100.
- ‡ Not all combinations of temperature ratings and wax finishes are Approved or Listed. Check specific submittals for combinations. V27 and V34 models are MEA (662-99-D) and CSFM (6769-0531, 112) Approved.
- § Approved for use on sloped ceilings.
- ** Reccessed pendent up to 1/2" (13 mm) adjustment; For rooms 12' x 12' ft. to 20' x 20' ft./3.7 x 3.7 m to 6.1 x 6.1 m.
- *** Reccessed pendent up to 3/8" (10 mm) adjustment; For rooms 12' x 12' ft. to 18' x 18' ft./3.7 x 3.7 m to 5.5 x 5.5 m.
- †† Also available with Sealing Gasket for Clean Room Applications. Request publication 4053.

Available temperature ratings

Victaulic Part Identification	Nominal Rating	Temperature - °F/C	Sprinkler Temperature Classification	Glass Bulb Color	Solder Link Color
A#	135	57	Ordinary	Orange	—
C	155	68	—	Red	—
D*	165	74	Ordinary	—	—
E	175	79	Intermediate	Yellow	—
F	200	93	Intermediate	Green	—
G	212	100	Intermediate	—	Black with White Dot/White Arms
J	286	141	High	Blue	Black with Blue Dot/Blue Arms
K	360	182	Extra High †	Purple	—
M	Open	—	†	Open	Open
N	162	72	Ordinary	—	Black

† Standard response only.
* 138F/59°C per LPCB
† Cover for use with a Standard or Quick Response Concealed Sprinkler 175F/79°C or 200F/93°F

FireLock Sprinklers – Dry

Dry

Note: Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.